



ATILIM
DEĞİRMEN MAKİNA

BLOVER İSTASYONU





BLOVER İSTASYONU

Pozitif deplasmanlı, 3 loblu, kapalı dişli kutusu içerisinde çift taraflı yağlamalı sistemli, şasesi, emniyet subabı, geri tepme (check) valf, vibrasyon takozları, temiz hava filtresi ve manometresi

Model	RPM	100 mbar		800 mbar	
		Os	N	Os	N
PF-46	850	1,02	0,75	0,18	3,70
	1950	2,73	2,20	1,88	5,50
PF-56	850	1,63	0,75	0,18	3,70
	1950	4,26	2,20	3,13	11,00
PF-71	850	2,15	2,20	1,14	5,50
	1950	5,86	3,70	4,85	11,00
PF-86	800	3,83	2,20	1,14	11,00
	1950	10,69	3,00	8,02	18,50
PF-106	850	5,69	2,20	3,34	15,00
	1950	15,33	3,70	12,98	30,00
PF-121	780	8,29	3,0	4,39	11,00
	1850	21,43	5,5	16,87	30,00
PF-136	780	11,73	3,70	7,17	22,00
	1850	30,94	7,50	26,38	55,00
PF-165	780	15,04	5,50	9,72	30,00
	1850	39,81	11,00	23,04	75,00
PF-205	620	24,30	11,00	16,70	55,00
	1390	59,50	18,50	51,67	110,00

